



MINI PTZ MK 2

Integrated High Resolution Color CCD Inspection Camera Systems with High Intensity Lighting and Multi-Function Controllers (Integrated Recorder option available)



Nuclear
Power



Homeland
Security
& Defense



Industrial and
Manufacturing



Healthcare



Labs and
Education

OVERVIEW

The Mini PTZ Mk2 provides a complete inspection system including a sealed, underwater capable, high performance, pan/tilt/zoom color CCD camera.



KEY FEATURES

- Compact housing allows deployment through openings as small as 65 mm diameter (2.56")
- Outstanding viewing performance achieved by using a high performance CCD module with 10:1 optical and 4:1 digital variable speed zoom
- Continuous pan and +/- 120° tilt, each with variable speed which can automatically reduce as the camera is zoomed in
- High-intensity white LED lighting with independently controllable 'spot' and 'flood' lights
- Position feedback system to provide for preset positioning and adjustable end stops
- Slip clutch for fail-safe retrieval
- Optional high power tracking light for underwater use
- Rack mounted controller with remote control capability or optional folding case, portable controller with integrated flat screen monitor
- Available with integrated video recorder
- Connection to Dotcam

SPECIFICATIONS AND PERFORMANCE

Camera	
Image Sensor	1/4" EX-view HAD CCD™
Temperature Rating (camera module)	0 - 50 °C (32 - 122 °F)
Resolution	NTSC 470 TV lines PAL 460 TV lines
Zoom	10:1 optical (4.2 mm - 42 mm) 4:1 digital
Focus	Manual or auto
Angle of View (H)	46° (Wide) to 5° (Tele)
Minimum Object Distance in Air	10 mm (0.4") wide angle 1000 mm (39") narrow angle
Minimum Object Distance in Water	13 mm (0.5") wide angle 1330 mm (52") narrow angle
Iris Control	Manual or Auto
Overall Dimensions	Diameter: 63.5 mm (2.5") Length: 345 mm (13.6")
Construction	Stainless steel housing
Weight	2.4 kg (5.3 lbs)
Depth Rating	60 m (197')
Radiation Tolerance	100 Gy [⁶⁰ Co] (H ₂ O) 10 ⁴ rad [⁶⁰ Co] (H ₂ O)
Operating Dose Rate	100 Gy/h (10 ⁴ rad/h)
Range - Pan	Continuous
Range - Tilt	+/-120°

Lighting	
LEDs x 4 (Spot)	Beam Angle 12°. Up to 550 lx at 1 m
LEDs x 4 (Flood)	Beam Angle 30°. Up to 200 lx at 1 m

External lamps (tracking) available.

CAMERA CONTROL UNIT SPECIFICATIONS

Available as 19" Rack or Portable Pelicase Version.

19" Rack Mount Unit for Fixed Installations	
Dimensions	483 mm W x 88 mm H x 353 mm D (19.1" W x 3.5" H x 14" D)
Weight	5 kg (11 lbs)

Robust Portable Self Contained Unit with Integrated Flat Screen Monitor & Video Recorder	
Dimensions (case closed)	406 mm W x 330 mm H x 174.5 mm D (16" W x 13" H x 16.9" D)
Dimensions (case open)	406 mm W x 330 mm H x 443 mm D (16" W x 13" H x 17.4" D)
Weight	8.5 kg (18.7 lbs)

Camera Control: Features/Benefits	
Video Outputs	S-Video* Composite

* 19" rack mount unit only

> UK - FARNBOROUGH

Mirion Technologies (IST) Ltd
2 Columbus Drive, Farnborough, Hampshire, GU14 0NZ
T: +44 1252 375137 | F: +44 1252 391890 | E: MirionUK@mirion.com

> FRANCE - LAMANON

Mirion Technologies (MGPI) SA
Route d'Eyguières, FR - 13113 Lamanon
T: +33 490 595959 | F: +33 490 595518 | E: rees.sales@mirion.com

> GERMANY - BONN

Mirion Technologies
Kaiser-Konrad-Str 93a, D53225, Bonn
T: +49 228 625088 | F: +49 228 626 300 | E: rees.sales@mirion.com

> CHINA - BEIJING

Mirion Technologies
15/F, Office Building A, Parkview Green, 9 Dongdaqiao Road,
Chaoyang District, Beijing 100020
T: 0086 139 1163 6957 | E: away@mirion.com

> USA - NEW YORK

Mirion Technologies (Imaging) LLC
315 Daniel Zenker Drive, 200 IST Center, Horseheads, NY 14845
T: +1 607 562 4369 | T: +1 800 432 1478 | F: +1 607 562 4392
E: isdnuclearusa@mirion.com

For additional information, please contact your Mirion Technologies representative; for any country not listed, email rees.sales@mirion.com.

Copyright © 2017 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners.

Specifications may vary according to system configuration. We reserve the right to modify or amend the information herein without prior warning. Please contact your Mirion representative for further information.

Mirion Technologies (IST) Ltd and Mirion Technologies (Imaging), LLC are ISO 9001:2008 certified companies (certificates available on request or at www.mirion.com).

Please note that the products and accessories described in this data sheet may be subject to UK export control or US re-export control. Please check with your authorized representative when enquiring about this product.